



## Rotary Valves

- Feeding and mining of pulverulent and granular products
- Range of machines that can process capacities from 5 to 450 m<sup>3</sup>/h
- Driving geared motor and elastic coupler
- Standard and high vacuum execution
- Special concept allowing the passage of large gradings

# Rotary Valves

Flange dimension

Type	L mm	w mm	H mm	Input - mm		Output - mm		Capacity m <sup>3</sup> /h	Motor kW	Δp Allowed mbar	Mesh Size mm
				L	w	L	w				



## Rotary valves (standard and high vacuum)

## Pulverulent product

10 L	675	494	356	232	256	232	256	9	0.55	50	40
10 HV	675	599	356	232	256	232	256	9	1.1	500	40
16 L	680	599	356	361	256	361	256	14	1.1	50	40
16 HV	680	718	356	361	256	361	256	14	1.1	500	40
45 L	811	877	500	569	288	569	288	40	2.2	50	40
45 HV	811	998	500	569	288	569	288	40	2.2	500	40



## Rotary valves

## Pulverulent and granular product

045 -Z	1,920	510	544	500	185	650	205	40	1.5	120	40
048 -Z	2,120	510	544	800	185	950	205	65	1.5	120	40
0410 -Z	2,420	510	544	1,000	185	1,150	205	80	1.5	120	40
056 -Z	2,070	675	655	600	220	750	250	75	2.2	120	50
058 -Z	2,265	675	655	800	220	950	250	100	2.2	120	50
0510 -Z	2,465	675	655	1,000	220	1,150	250	125	3	120	50
066 -Z	2,080	780	880	600	290	750	320	110	2.2	120	60
068 -Z	2,320	780	880	800	290	950	320	150	3	120	60
0610 -Z	2,560	780	880	1,000	290	1,150	320	190	3	120	60
086 -Z	2,710	990	1,094	620	395	760	425	200	5.5	120	80
088 -Z	2,910	990	1,094	820	395	960	425	265	5.5	120	80
0810 -Z	3,110	990	1,094	1,020	395	1160	425	330	5.5	120	80



## Rotary valves with mobile screen

## Pulverulent and granular product that can contain big pieces

044 -ZS	1,985	840	710	400	240	560	350	30	1.5	-	100
045 -ZS	2,085	840	710	500	240	660	350	40	1.5	-	100
048 -ZS	2,231	840	710	820	240	960	650	65	1.5	-	100
056 -ZS	2,044	790	684	600	219	750	249	75	2.2	-	100
058 -ZS	2,405	940	810	800	340	960	400	100	3	-	100
0510 -ZS	2,566	940	810	1,000	340	1,160	400	125	3	-	100
066 -ZS	2,175	1,062	1,015	600	417	770	670	110	4	-	200
068 -ZS	2,375	1,062	1,015	800	417	970	670	150	4	-	200
0610 -ZS	2,575	1,062	1,015	1,000	417	1,170	670	190	4	-	200
086 -ZS	2,710	1,262	1,215	600	567	770	820	200	5.5	-	300
088 -ZS	2,910	1,262	1,215	800	567	970	820	265	5.5	-	300
0810 -ZS	3,110	1,262	1,215	1,000	567	1,170	820	330	5.5	-	300
0815 -ZS	3,370	1,262	1,215	1,500	567	1,660	820	450	7.5	-	300

Besides his line of rotary valves has KH Mineral also a wide range of pendulum flap gates witch can be used in many fields.

### ThyssenKrupp KH Mineral SAS

Parc Industriel Sud - ZI Neuwald  
1, rue René François Jolly  
B.P. 70537

F-57205 Sarreguemines

Tél. (33) 03 87 98 73 73 - Fax (33) 03 87 98 89 18 ou (33) 03 87 95 40 73

Email : [contact@khmineral.com](mailto:contact@khmineral.com)

Internet : [www.khmineral.com](http://www.khmineral.com)

